

**For .250" (6.35mm) to 4.5" (114.3mm) OD tubing up to .250" (6.35mm) wall thickness**

Tri Tool's Model 304 offers easy set-up and operation with the accuracy required to consistently achieve perfectly flat, square and burr free ends. The cutting head allows installation of up to 3 tool bits for squaring, beveling or special preps, and the bench stand is easily removable for portable use.



*The 304 is the ideal companion to high purity autogenous orbital welding equipment.*

## FEATURES

- Quick-change Stainless saddle clamping (no special tools required)
- Open, high visibility design for increased productivity
- Integral clear chip guard
- Precision graduated feed
- Variable speed, dual range drive motor for optimal cutting speed
- Rugged foam-lined storage case

## OPTIONS

- Fast and easy pneumatic clamping (with hand or foot actuation)
- Custom saddle sets for fittings
- Choice of a high torque electric, pneumatic, or sealed DC drive motor

## QUICK SPECS

- Saddle Clamping Length: .875" (22.2mm)
- Short Perch Clamping Length: .250" (6.35mm)  
\*Short Perch Saddles
- Tool Bit Travel: .560" (14.2mm)
- Weight: 18.25 lbs. (8.28 Kg)
- AC Power: 120VAC, 220VAC

*Note: Specifications subject to change without notice.*



The integral, clear chip guard is designed to provide increased operator safety.